

Certificate of conformity of the factory production control



Number	0620-CPR-58521/05	Replaces	0620-CPR-58521/04
Issued	2016-10-06	First issued	2010-11-10

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Hot rolled products of structural steels

Scope of certificate:

whereby the scope of construction product (s) is listed on page 2 of this certificate of conformity

placed on the market under the name or trademark of

ÇOLAKOĞLU METALURJİ A.Ş.

and produced in the manufacturing plant

Dilovası Kocaeli -TURKEY

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 10025:2004

under system 2+ are applied and that **the factory production control is assessed to be in conformity with applicable requirements.**

This certificate was first issued on 2010-11-10 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

Luc Leroy
Kiwa

Advise: consult www.kiwa.nl to check whether the certificate is valid.

Notified Body No. 0620

Kiwa Nederland B.V.

Sir Winston Churchillaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 (0) 88 998 44 00

Fax +31 (0) 88 998 44 20

info@kiwa.nl

www.1kiwa.com

Manufacturer

ÇOLAKOĞLU METALURJİ A.Ş.

Dil Iskelesi Dilovası Kocaeli -TURKEY

Phone (+90-262) 641 50 50 pbx

Fax (+90-262) 641 41 11

Manufacturing plant

ÇOLAKOĞLU METALURJİ A.Ş.

Dil Iskelesi Dilovası Kocaeli -TURKEY

Phone (+90-262) 641 50 50 pbx

Fax (+90-262) 641 41 11

kiwa
Approved



Certificate of conformity of the factory production control



0620-CPR-58521/05

Scope of certificate:

Product	Dimensions	Quality
COILS	Thickness from 1 mm to 26 mm	S235JR, S235J0, S235J2, S235JRC, S235J0C, S235J2C
		S275JR, S275J0, S275J2, S275JRC, S275J0C, S275J2C
		S355JR, S355J0, S355J2, S355JRC, S355J0C, S355J2C
	Thickness from 1 mm to 12 mm	S355J0WP, S355J2WP

* Including delivery condition +N and AR